

Product Name :
Semi-Automatic Penetrometer For Testing Lab for Bitumen Testing Lab

Product Code :
NBTE-M5



Description :

Semi-Automatic Penetrometer for Bitumen Testing - Used to determine grade of bitumen. The penetration tests determine consistency of bitumen for the purpose of grading. Depth in units 1/10 of millimeter to which a standard needle having a standard weight will penetrate vertically in a duration of five seconds at a temperature of 25C determines penetration for gradation.

Compact with timer to control duration of penetration. The instrument is provided with lead screw gear arrangement, Leveling screws, Spirit level. The head, together with dial plunger rod a cone (or needle) slides on a pillar and can be clamped at any desired height. A rack and pinion and pointer assemble provides fine adjustment of needle or cone tip to sample. It incorporates a clutch mechanism. Which makes reading of penetration and subsequent resetting a simple and accurate operation. The dial is graduated in 400 1/10 and the millimeter subdivisions and the needle pointer against figures makes easy reading. Supplied with a bitumen penetration needle, ring weight one each 50 gms. and 100 gms. two sample containers.

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773