

Product Name :
Standard Tar Viscometer For Testing Lab

Product Code :
NPPT-M7



Description :

Standard Tar Viscometer - For determining the viscosity of cut back bitumen and road oil. The viscometer consists of a chrome plated copper bath, with a drain valve and a central tube to receive the test cup and to position the stirrer, and is mounted on a stand with levelling feet. Stirrer has a curved shield and is provided with an insulated handle, thermometer socket and swivel support for the valve. Supplied complete with 10 mm cup and ball valve or 4 mm cup and ball valve as per the model required.

The following models are available :

- Standard Tar Viscometer, Electrical Heating with Immersion Heating Elements and Dimmerstat for controlling the temperature. Suitable for operation on 220 V, 50 Hz, single phase, AC supply. Complete with 10 mm cup and valve.
- Standard Tar Viscometer, Electrical Heating similar as above, but with 4 mm cup and valve.

Replacement Parts

- Cup, 10mm
- Ball valve, 10mm
- Cup, 4mm
- Ball valve, 4mm

Extras

- Thermoemter IP 8C, Range : 0°C to 45°C
- Thermoemter IP 9C, Range : 40°C to 85°C
- Thermoemter IP 10C, Range : 76°C to 122°C

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773